

STERİL-ENDİREK PANEL ARMATÜRLER

CLEAN - SIVA ALTI



GÜÇ(watt)	15	20	40	40	70
IŞIK RENGİ	3000-4000-6500K				
IŞIK AKIŞI (LÜMEN)	1.560	2.080	4.160	4.160	7.280
VERİMLİLİK (LM/W)	104	104	104	104	104
ARMATÜR ÖLÇÜLERİ (mm)	295x295x70	295x595x70	295x1195x70	595x595x70	595x1195x70
ÜRÜN AĞIRLIK (KG)	3	6	9	9	12



CLEAN SIVA ÜSTÜ



GÜÇ(watt)	15	20	40	40	70
IŞIK RENGİ	3000-4000-6500K				
IŞIK AKIŞI (LÜMEN)	1.560	2.080	4.160	4.160	7.280
VERİMLİLİK (LM/W)	104	104	104	104	104
ARMATÜR ÖLÇÜLERİ (mm)	300x300x70	300x600x70	300x1200x70	600x600x70	600x1200x70
ÜRÜN AĞIRLIK (KG)	3,6	7	9,6	9,6	13



TWİN - SIVA ALTI



GÜÇ(watt)	40	55
IŞIK RENGİ	3000-4000-6500K	
IŞIK AKIŞI (LÜMEN)	3.600	4.950
VERİMLİLİK (LM/W)	90	90
ARMATÜR ÖLÇÜLERİ (mm)	595x595x110	595x595x110
ÜRÜN AĞIRLIK (KG)	4,37	4,37



TWİN - SIVA ÜSTÜ



GÜÇ(watt)	40	55
IŞIK RENGİ	3000-4000-6500K	
IŞIK AKIŞI (LÜMEN)	3.600	4.950
VERİMLİLİK (LM/W)	90	90
ARMATÜR ÖLÇÜLERİ (mm)	600x600x110	600x600x110
ÜRÜN AĞIRLIK (KG)	5,68	5,68

